

Double Reverse Appliqué, Full Day Class
© 2020 Ellen Lindner, www.AdventureQuilter.com
Virtual (ZOOM) Class

NOTES:

- This class is geared toward the intermediate level quilter, who is comfortable with free motion sewing.

Supply List:

Equipment:

Sewing machine that can lower its feed dogs

Presser foot for free motion (darning, big foot, etc.)

Light box (This is integral to the procedure. If you don't have a light box, plan to use a bright window or some other easy tracing set up.)

Sharp embroidery scissors (the little ones that are sharp all the way to the tip)

Paper scissors

General sewing supplies

Fat highlighter

Black Sharpie, regular tip

5+ colored pencils, each a different color

If you want to learn how to make your own patterns:

A favorite color photo, with strong light/dark contrasts. An 8 x 10 is best.

Tracing paper, several pieces.

Pencil and eraser

(Optional, but highly recommended) Send a digital version of your photo to Ellen at

elindner@cfl.rr.com . She needs it at least 5 days before the start of class.

Fabrics, threads, and such:

*Sulky Totally Stable (or other lightweight iron-on stabilizer that can be torn away later)

Thin white fabric (like muslin) for the bases, 2 pieces, each ~ 14 x 14

See color placement chart for fabric colors and quantities.

- Small scale or subtle prints work well for the apple. Background and shadow fabrics can be larger prints, if desired.
- **Directions are given for red and green fruit, however, other colors are very stunning*. When choosing fabrics for a different color scheme, match the value (light vs. dark,) to the color stated on the pattern.**

Clear monofilament thread

Medium gray thread (OR threads that loosely match your fabrics)

Class Preparation: Do the following steps twice - once for the apple and once for the pear. (Be ready to sew both, but we will start with the apple.)

Join two pieces of stabilizer together, to create a piece at least 14 x 14. (Overlap the pieces and iron the overlapped area. Pin, on the non-fusible side, for security.)

Print out all four parts of the pattern. Trim the interior margins. Using a light box, align the pieces correctly and tape them together.

Using a black Sharpie, trace the pattern lines (but not the numbers) onto the non-fusible side of the stabilizer.

Using a pen or pencil, add the pattern numbers.

Put the stabilizer, fusible side down, onto the white base fabric. Iron the two together.

Iron all fabrics. Label fabrics and stack them in order (You can write in one corner. See the number-color chart on the pattern.)

Set up your machine with monofilament in the bobbin and gray thread on top. Increase the top tension to approximately 7.

[*See the Double Reverse Appliqué gallery](#)

Email me if you have questions: ellen@adventurequilter.com